# Conditioner





## When optimal means optimal



### It's different for everyone

Optimal pellet quality depends heavily on precision thermo-mechanical preconditioning. Or simply put, pellet quality starts in the conditioner. CPM understands this well, but we also know that "optimal" isn't the same for everyone.

Quality pellets are a result of just the right combination of moisture, temperature, and retention time. That's why you need a conditioner with plenty of flexibility, so your end pellets are the best they can be.

CPM offers a market-leading conditioner that gives you maximum performance and flexible configuration-specific to the materials you're pelleting. All with the lowest operating costs on the market today.

### **Excellent moisture absorption and** temperature increases

Moisture absorption and temperature increases are critical to the quality of your finished pellet. CPM's conditioner adds steam in high volumes at low velocity, ensuring temperature increases and retention times are ideal throughout the pelleting process.

### Ideal mixing and retention times

How long the material remains in the conditioner depends on your unique end-pellet requirements. Time and temperature combine to drive moisture and heat into the center of the material. CPM conditioners deploy wide, adjustable paddles to ensure consistent mixing and the best possible conditioned material.

### **Flexible configurations for unique** plant layouts

Not every plant has the same layout or size, and as most process operators know, space is valuable. CPM conditioners enable single or stacked configurations, so you can maximize your available space. And to ensure conditioning is optimized, we have flexible, or available, mounting options within your plant's vertical or horizontal limitations.

### **Convenient design for access and** maintainability

CPM conditioners have uniquely hinged inspection covers that give you easy access to the paddles and settings. This ensures that adjustments can be made to the paddle configurations quickly, easily, and safely.

### Maximum conditioning—hands down Highly customizable and highly reliable

Because the needs and configurations of a process plant Not all processing conditions are identical. At CPM, we know vary, CPM conditioners are custom manufactured to your that different materials require different conditioning, which plant's needs. Gear reducer drives can be added to either is why our conditioners come with shaft speeds ranging the inlet or the discharge end; hinged inspection covers can between 65 and 200 RPM. You can then maximize the be placed on the left or right side; and steam can be piped mixing of steam, water, and other liquids to ensure your to the conditioner on either side. final pellets are optimal for your purpose.



**CPM** Conditioner

Inspection covers for easy access and adjustment

### Whatever your needs are, we have a conditioner to fit



## **Specifications and Dimensions**

CPM Model	Conditioning Diameter X Length*	Standard HP
18INF6.5	18" x 6.5' (457 x 1981 mm)	7.5
18INF8.5	18" x 8.5' (457 x 2591 mm)	10
18INF10	18" x 10' (457 x 3048 mm)	15
24LTC8	24" x 8' (610 x 2438 mm)	15
24LTC10	24" x 10' (610 x 3048 mm)	20
24LTC12	24" x 12' (610 x 3658 mm)	25
30LTC10	30" x 10' (762 x 3048 mm)	25
30LTC13	30" x 13' (762 x 3962 mm)	30
30LTC16	30" x 16' (762 x 4877 mm)	40
36LTC10	36" x 10' (914 x 3048 mm)	30
36LTC13	36" x 13' (914 x 3962 mm)	40
36LTC16	36" x 16' (914 x 4877 mm)	50
36LTC20	36" x 20' (914 x 6096 mm)	60

\*Approximate dimensions

© 2018 CPM. California Pellet Mill is a division of CPM Inc. For more, visit CPM.net

### **CONTACT US**

To learn more about our conditioners and other processing equipment, contact a CPM representative or visit CPM.net today.

### **California Pellet Mill**

1114 E. Wabash Ave. Crawfordsville, IN 47933 Ph: 765-362-2600 800-428-0846 Fax: 765-364-8010

### **CPM Europe**

Rijder 2 1507 DN Zaandam The Netherlands Ph: 31 (0)75 6512 611 Fax: 31 (0)75 6512 600

### **CPM/Pacific Private Ltd.**

21 Gul Drive Singapore 629470 Republic of Singapore **Ph:** 65-6265-0701 **Fax:** 65-6268-6428

### CPM Machinery (Wuxi) Co. Ltd.

No. 10 Xindu Road Wuxi-Singapore Industrial Park Jiangsu Province People's Republic of China Ph: (86) 0510 85280487/ 85282240 Fax: (86) 0510 85282429

### Crown Iron Tecnologias LTDA

Avenida Sabiá, 758 Moema São Paulo – SP 04515-001 **Ph:** 55-11-3074-4099

### **CPM Argentina**

Alberto J. Paz 1065 Bis P.B. Of. 5 y 6 Complejo Fisherton Plaza Mall Rosario (2000) - Santa Fe, Argentina **Ph:** +54-341-459-6966 **Fax:** 54-341-459-6970 Op #104





